# Safety data sheet Intense Copper - Luster Pigment

Revision date : 7/23/2014 Version: 1.0 Page: 1/6 (30322671/SDS\_GEN\_US/EN)

## 1. Substance/preparation and company identification

<u>Company</u> Aardvark Colors 245 Kent Ave. Brooklyn, NY 11249 USA 24 Hour Emergency Response Information CHEMTREC: 1-800-424-9300

# 2. Composition/information on ingredients

CAS Number	•
12001-26-2	
1309-37-1	

<u>Content (W/W)</u> 45.0 - 86.0 % 14.0 - 55.0 % <u>Chemical name</u> Mica-group minerals Iron oxide

## 3. Hazard identification

## Emergency overview

CAUTION: PROLONGED OR REPEATED EXPOSURE TO DUST MAY CAUSE PULMONARY PROBLEMS.

#### Potential health effects

#### Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

#### Irritation:

Inhalation of dust may cause respiratory tract irritation, coughing and breathing difficulties. Contact with the eyes or skin may cause mechanical irritation.

#### Repeated dose toxicity:

Prolonged or repeated exposure may cause pulmonary problems.

#### Potential environmental effects

#### Aquatic toxicity:

At the present state of knowledge, no negative ecological effects are expected.

# 4. First-aid measures

General advice: Remove contaminated clothing.

Revision date : 7/23/2014 Version: 1.0

#### If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

#### If on skin:

Wash thoroughly with soap and water. If irritation develops, seek medical attention.

#### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. If irritation develops, seek immediate medical attention.

#### If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Seek medical attention if necessary.

#### Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## 5. Fire-fighting measures

Flash point: Autoignition: Flammability:

does not ignite

not applicable not applicable

Suitable extinguishing media: dry extinguishing media, foam

Unsuitable extinguishing media for safety reasons: carbon dioxide

#### Hazards during fire-fighting:

No particular hazards known.

#### Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

#### Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

If exposed to fire, keep containers cool by spraying with water.

## 6. Accidental release measures

#### **Personal precautions:**

Avoid dust formation.

Wear appropriate respiratory protection. Use personal protective clothing. Ensure adequate ventilation.

## **Environmental precautions:**

Do not empty into drains.

Revision date : 7/23/2014 Version: 1.0

Page: 3/6 (30322671/SDS GEN US/EN)

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

#### Cleanup:

For small amounts: Pick up with suitable appliance and dispose of. For large amounts: Pick up with suitable appliance and dispose of.

Spills should be contained and placed in suitable containers for disposal.

# 7. Handling and storage

## <u>Handling</u>

#### General advice:

Breathing must be protected when large quantities are decanted without local exhaust ventilation. Avoid contact with the skin, eyes and clothing.

Avoid dust formation. Closed containers should only be opened in well-ventilated areas.

#### Protection against fire and explosion:

No special precautions necessary.

See MSDS section 5 - Fire fighting measures. Prevent electrostatic charge accumulation.

#### Storage

#### General advice:

Keep in a cool place. Keep container dry.

## 8. Exposure controls and personal protection

## Components with workplace control parameters

OSHA	TWA value 20 millions of particles per cubic foot of air;
ACGIH	TWA value 3 mg/m3 Respirable fraction ;
OSHA	PEL 10 mg/m3 fumes/smoke ;
ACGIH	TWA value 5 mg/m3 Respirable fraction;
	ACGIH OSHA

#### Personal protective equipment

#### **Respiratory protection:**

Observe OSHA regulations for respirator use (29 CFR 1910.134). Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

#### Hand protection:

Chemical resistant protective gloves

#### Eye protection:

Safety glasses with side-shields.

#### General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Due to the colouring properties of the product closed work clothes should be used, to avoid stains during manipulation. Hands and/or face should be washed before breaks and at the end of the shift. Wash soiled clothing immediately.

# 9. Physical and chemical properties

Form:

Revision date : 7/23/2014 Version: 1.0

Page: 4/6 (30322671/SDS\_GEN\_US/EN)

		(30322671/SDS_GEN_US/EN)
Odour: Colour: pH value: Melting point: Boiling point:	odourless brown 6.0 - 11.0	( 4 %(m)) The substance / product decomposes. not applicable
Density: Relative density: Bulk density: Particle size: Solubility in water:	3.4 kg/l 3.4 146 kg/m3 6 - 48 μm	(approx. 20 °C) insoluble

# 10. Stability and reactivity

#### Hazardous reactions:

No hazardous reactions when stored and handled according to instructions. The product is chemically stable. Hazardous polymerization will not occur.

### **Decomposition products:**

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

#### Thermal decomposition:

No data available.

## 11. Toxicological information

## Acute toxicity

#### Oral:

LD50/rat: > 2,000 mg/kg The product has not been tested. The statement has been derived from the properties of the individual components.

#### Skin irritation:

May cause mechanical irritation.

### Eye irritation :

May cause mechanical irritation.

# 12. Ecological information

### Environmental fate and transport

#### **Biodegradation:** Evaluation:

The colourant is insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plant

## Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

## Environmental toxicity

Revision date : 7/23/2014 Version: 1.0

Page: 5/6 (30322671/SDS\_GEN\_US/EN)

## Other ecotoxicological advice:

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

## 13. Disposal considerations

#### Waste disposal of substance:

Must be dumped or incinerated in accordance with local regulations. Dispose of in a licensed facility. Do not discharge into drains/surface waters/groundwater. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

## Container disposal:

Uncontaminated packaging can be re-used. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

## 14. Transport information

Land transport USDOT

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

# 15. Regulatory information

Federal Regulations

**Registration status:** TSČA, US

released / listed

OSHA hazard category:

OSHA PEL established, ACGIH TLV established

SARA hazard categories (EPCRA 311/312): Acute

### State regulations

State RTK

CAS Number 12001-26-2 1309-37-1

**Chemical name** Mica-group minerals Iron oxide

State RTK MA, NJ, PA MA, NJ, PA

Revision date : 7/23/2014 Version: 1.0

Page: 6/6 (30322671/SDS\_GEN\_US/EN)

# 16. Other information

Flammability: 0

HMIS III rating Health: 1

Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.